

1. Application range

Lithium Manganese Dioxide cell battery, Model CR14505SE
Manufacturer: Wuhan HCB Battery Technology Co.,Ltd.


2. Objective

To regulate the performance index and test method of CR14505SE, as well as guidelines and warnings.

3. Technical parameter

- 3.1 Model:CR14505SE
- 3.2 Nominal voltage: 3.0V
- 3.3 Norminal capacity:1800mAh (Continuous discharging at 1mA until 2.0V end-voltage at 23±2℃)
- 3.4 Max. constant current: 10mA
- 3.5 Max. pulse current: 100mA
- 3.6 Operating temperature range: -40℃~+80℃
- 3.7 Nominal weight: 22.0g
- 3.8 Max. Outer dimensions: as drawing.
- 3.9 Structures: Manganese dioxide cathode、 lithium anode、 organic electrolyte、 polypropylene separator and steel battery can and cap.
- 3.10 Self-discharging rate: ≤1% per year.

4. Discharge curve



5. International attestation



ISO-16628



EU 02

031073 01



MH10060

RoHS

No.03007

6. Application

Radio communication transmitter-receiver, underwater weapons, medical instruments,RFID active tag/card, automatic sanitaryware, intelligent IC card, PC computer RAM,CMOS memory backup powersupply, portable communication equipment,time counter, number counter and so on.