



1. Application range

Lithium Manganese Dioxide cell battery, Model CR26500
Manufacturer: Wuhan HCB Battery Technology Co.,Ltd.

2. Objective


To regulate the performance index and test method of CR26500, as well as guidelines and warnings.

3. Technical parameter


- 3.1 Model:CR26500
- 3.2 Nominal voltage: 3.0V
- 3.3 Norminal capacity:5000mAh (Continuous discharging at 10mA untill 2.0V end-voltage at $23\pm 2^{\circ}\text{C}$)
- 3.4 Max. constant current: 2000mA
- 3.5 Max. pulse current: 3000mA
- 3.6 Operating temperature range: $-40^{\circ}\text{C}\sim +80^{\circ}\text{C}$
- 3.7 Nominal weight: 62.0g
- 3.8 Max. Outer dimensions: as drawing.
- 3.9 Structures: Manganese dioxide cathode、 lithium anode、 organic electrolyte、 polypropylene separator and steel battery can and cap.
- 3.10 Self-discharging rate: $\leq 1\%$ per year.

4. Discharge curve

Discharge performance



The relationship between Voltage and temperature



5. International attestation



ISO-16628



031073 01



MH10060

RoHS

No.03007

6. Application

Radio communication transmitter-receiver, underwater weapons, medical instruments,RFID active tag/card, automatic sanitaryware, intelligent IC card, PC computer RAM,CMOS memory backup powersupply, portable communication equipment,time counter, number counter and so on.